

# TLT632AF

## Ultra-thin small scissor lift

### Features

- Ultra-thin 3t small scissor vehicle lift.
- The platform is extendable.
- Ultra-thin structure design is applicable for on-ground arrangement ,technical cooperation with .Italy ,four hydraulic cylinders design ,convenient for demounting tyres and repairing chassis.
- Hydraulic interlocking and anti-explosion safety device makes it stable and reliable operation.
- Bilateral hydraulic synchronizing system ensures high synchronization performance.
- Travel limit safety device ,protects machine from being damaged.
- All moving points adopt automatic lubricating oil-free bearing for ensuring long lifespan.
- Oil hose anti-explosion device.
- CE-STOP function with safety alarm beep would automatically warn operators to keep safe distance from lift when it lowers to 400mm high from ground.
- CE certificated



### Technical parameters

Rated load:	3200kg
Lifting height:	2000mm
Initial height:	≤110mm
Lifting time:	≤60s
Lowering time:	≥20s
Runway width :	620mm
Runway length :	1460~2060mm
Advised distance between two runways:	800mm
Overall width:	2040mm
Safety method :	Mechanical safety lock + pneumatic release
Motor power :	2.2kw
Motor voltage:	3 phase/380v or Single phase/220V

### Optional parts

High brightness LED band



### Environmental Requirement

Working temperature :	-5°C ~+40°C
Transport/storage temperature :	-5°C ~+ 40°C
Relative humidity :	Temperature+ 30°C ,relative humidity 80 %
Height above sea level:	No more than 2000m

### Overall size

